

Vertical splitter 6/ 7 tons - FB506TF - FB507TF series

SPLITTING RANGE

■ FB5006TF - FB507TF series

- 2-hand control with wood holding claw
- Integrated phase inverter (400 V)
- Safety circuit breaker
- Big wheels for easy transporting
- Adjustable cylinder stroke up to 50 cm
- High return speed
- Fix splitting table
- Storage space on both sides
- Robust and durable design



FB507TF



FB506TF



Ø 45 cm
< 50 cm >



Safety circuit breaker



2-hand control with wood holding claw

| Log splitter | FB506TF M | FB506TF T | FB507TF M | FB507TF T |
|-------------------------------------|----------------|----------------|----------------|----------------|
| Splitting force (to) | 6 | 6 | 7 | 7 |
| Splitting length (cm) | 55 | 55 | 55 | 55 |
| Power supply | 230 V / 2.2 kW | 400 V / 2.2 kW | 230 V / 2.2 kW | 400 V / 2.2 kW |
| Splitting speed (cm/s) | 5 | 5 | 4.75 | 4.75 |
| Return speed (cm/s) | 16,7 | 16,7 | 12,5 | 12,5 |
| Oil tank capacity (L) | 4,75 | 4,75 | 10 | 10 |
| Pump output (L/min) | 7,5 | 9 | 7,5 | 9 |
| Dimension (HxLxB cm) | 123 x 54 x 80 | 123 x 54 x 80 | 123 x 65 x 85 | 123 x 65 x 85 |
| Weight (kg) | 125 | 125 | 137 | 137 |
| Split-wedge FB506/507 (ECL000301) | | | | |
| 400 V female plug (PRI00002) | | | | |